

12" WIDE
WHITE
OVERLAID
PAVEMENT
STRIPE

10'
MINIMUM
8'
MINIMUM

NEW ASPHALT
PAVEMENT
SECTION

SEE ENLARGED
VIEW BELOW

SECTION A-A NEW PAVEMENT

1/2" PREMOULDED
EXPANSION JOINT
MATERIAL

2" 9.5 F2 TOP
COURSE HMA, 80
SERIES COMPACTION

TACK COAT

FULL DEPTH
SAW CUT

11" CLASS C
CONCRETE

6" SUBBASE
COURSE TYPE 1

12" WIDE
WHITE
OVERLAID
PAVEMENT
STRIPE

10'
MINIMUM
8'
MINIMUM

SEE ENLARGED
VIEW BELOW

SECTION A-A EXISTING PAVEMENT

CONCRETE
COLLAR

HARDWOOD SHIMS

2" DIAMETER WEEP HOLE FILL
WITH SETTING BED MATERIAL

CONCRETE STREET PAVER

3/4" MINIMUM WASHED 1A COARSE
AGGREGATE SETTING BED MATERIAL

CRADLE

4" PERFORATED
CORRUGATED
POLYETHYLENE
UNDERDRAIN PIPE
AND UNDERDRAIN
FILTER MATERIAL

ENLARGED VIEW

NOTES:

1. CONCRETE CRADLE TO BE POURED
INTEGRALLY WITH COLLAR USING
CLASS E OR F CONCRETE.
2. SEE DETAIL S506-3.

CITY OF ROCHESTER

CONCRETE STREET PAVER CROSSWALK SECTIONS

ISSUED	2-13-06	NON-STANDARD
REVISED	7-31-12	DWG.NO.S506-4