



CONCRETE CURB




ELEVATION AT EXPANSION JOINT

NOTES:


- USE CLASS K CONCRETE FOR CONVENTIONALLY FORMED CONCRETE CURB - CLASS J CONCRETE FOR MACHINE FORMED CONCRETE CURB.
- BOTTOM OF CONCRETE CURB AND CONCRETE BASE TO BE AT SAME ELEVATION.
- 3. EXPANSION JOINTS TO BE ³/4INCH WIDE SPACED EVERY 20 FEET AND AT ALL IMMOVABLE OBJECTS. FILL JOINTS WITH PREMOLDED RESILIENT JOINT FILLER MATERIAL.
- 4. CURB REVEAL FOR HEADER CURB AT DRIVEWAY APRONS IS 11/2INCHES, AT SIDEWALK ACCESS RAMPS O INCHES.
- 5. TACK COAT TO BE APPLIED BETWEEN ALL LIFTS OF HMA COURSES AND ON TOP OF CONCRETE BASE.
- 6. PAVEMENT SEAMS TO BE SEALED WITH BITUMINOUS SEALER IN ACCORDANCE WITH NYSDOT MATERIAL DESIGNATION 702-0700.



CONCRETE CURB AT RIGID PAVEMENT



ELEVATION AT CONSTRUCTION JOINT



SECTION AT DOWEL

CITY OF ROCHESTER

CONCRETE CURB

ISSUED 9-2-91 STANDARD REVISED 12-30-11 DWG.NO.R609-5